

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings of claims in the application:

LISTING OF CLAIMS

1-17 (**Canceled**).

18. (**Currently Amended**) ~~An improved method for~~ Method of assigning one or more spreading sequences among a family of spreading sequences to a user of a ~~Multi-carrier Code Division Multiple Access~~ transmission network, each element of said sequence being, at the level of a transmitter of said network, each element of said spreading sequence being multiplied by a data item to be transmitted and then transmitted on a corresponding sub-carrier, ~~wherein the improvement comprises~~ comprising:

assigning, to the said user, said one or more spreading sequences, so as to minimize a function representing the interference between said one or more sequences, on the one hand, and spreading sequences of a predetermined set, on the other hand, said predetermined set being included in said family of spreading sequences at least one spreading sequence, and utilizing a minimization function to minimize the interference caused between the at least one sequence assigned to the user and a predetermined

~~set of spreading sequences assigned by the transmitter.~~

19. **(Previously presented)** A method according to claim 18 wherein the predetermined set of spreading sequences includes the set of sequences which are used by the network at the instant of assigning.

20. **(Previously presented)** A method according to claim 18 wherein the predetermined set of spreading sequences includes the set of sequences which are potentially usable after the instant of assigning.

21. **(Previously presented)** A method according to claim 18 wherein said set of spreading sequences includes a favored set of spreading sequences.

22. **(Currently Amended)** A method according to claim ~~1~~ 18 which further includes allocating, from among all the spreading sequences available at the instant of the assigning, the spreading sequence $c^{(i)}$ which minimizes a function $J^{(j,\Omega_k)}$ representing the interference between the spreading

sequence $c^{(i)}$ and the spreading sequences of the predetermined or given set, the sequence of rank i thus being assigned if this rank i verifies the following relationship:

$$i = \arg \min_j [J^{(j, \Omega_k)}]$$

where Ω_k is the set of the indices of the sequences of the predetermined or given set and Ω_j is the set of the indices of the available sequences.

23. **(Previously presented)** A method according to claim 18 wherein each user is assigned a spreading sequence so as to take into account the transmission quality envisaged for the spreading sequence.

24. **(Previously presented)** A method according to claim 23, wherein the user is assigned a spreading sequence $c^{(i)}$ which minimizes the cost function $J^{(j, \Omega_k)}$ with the spreading sequences $c^{(k)}$ of a predetermined or given set of sequences of index k belonging to a set Ω_k to a user desiring an average transmission quality, the spreading sequence $c^{(i)}$ which gives an

average value to the cost function $J^{(j, \Omega_k)}$ with the spreading sequences $c^{(k)}$ of a predetermined or given set of sequences of index k belonging to a set Ω_k and to a user whose transmission quality can be a minimum, a spreading sequence $c^{(i)}$.

25. **(Previously presented)** A method according to claim 22, characterized in that the cost function $J^{(j, \Omega_k)}$ representing the interference between the spreading sequence $c^{(i)}$ and sequences $c^{(k)}$ of indices k belonging to a set Ω_k is defined as being equal to the maximum value taken by a function $D^{(j, k)}$ representing the degradation of the transmission which is induced as a result of the interference between the spreading sequence $c^{(i)}$ and the spreading sequence $c^{(k)}$:

$$J^{(j, \Omega_k)} = \max_{k \in \Omega_k} D^{(j, k)}.$$

26. **(Previously presented)** A method according to claim 22 wherein the cost function $J^{(j, \Omega_k)}$ representing the interference between the spreading sequence $c^{(i)}$ and K sequences $c^{(k)}$ of indices k

belonging to a set Ω_k is defined as being equal to the average of the values taken by a function $D^{(j,k)}$ representing the degradation of the transmission which is induced as a result of the interference between the spreading sequence $c^{(j)}$ and the sequence $c^{(k)}$:

$$J^{(j,\Omega_k)} = \frac{1}{K} \sum_{k \in \Omega_k} D^{(j,k)} .$$

27. **(Previously presented)** A method according to claim 25 wherein the degradation function $D^{(j,k)}$ is defined as follows:

$$D^{(j,k)} = E \left[\left(\sum_{m=1}^M h_m^{(j)} c_m^{(j)} c_m^{(k)} \right)^2 \right] \quad \text{or} \quad D^{(j,k)} = E \left[\left(\sum_{m=1}^M h_m^{(k)} c_m^{(j)} c_m^{(k)} \right)^2 \right]$$

where E is the mathematical expectation, M the number of sub-carriers used in the MC-CDMA transmission system and $h_m^{(j)}$ is the apparent response of the transmission channel in view of an equalization process implemented in the receiver, the response for the frequency of the sub-carrier of rank m and for the receiver of the user of the sequence of rank j .

28. **(Previously presented)** A method according to claim 25 wherein the degradation function $D^{(j,k)}$ represents the small size of

the high-frequency components of a sequence $X^{(j,k)}$ of N elements resulting from the element-by-element product of the sequence $c^{(j)}$ and the sequence $c^{(k)}$.

29. **(Previously presented)** A method according to claim to claim 28 wherein the value of the degradation function $D^{(j,k)}$ is given by the application of a Fourier transform to the sequence $X^{(j,k)}$ of N elements resulting from the element-by-element product of the sequence $c^{(j)}$ and the sequence $c^{(k)}$.

30. **(Previously presented)** A method according to claim 28 wherein the value of the degradation function $D^{(j,k)}$ is given by the number of $\{+1, -1\}$ and $\{+1, -1\}$ transitions appearing in the sequence $X^{(j,k)}$ of N elements resulting from the element-by-element product of the sequence $c^{(j)}$ and the sequence $c^{(k)}$.

31. **(Previously presented)** A method according to claim to claim 18 wherein the method is implemented dynamically and includes re-assigning during transmission, at predetermined instants, the K - Q sequences still necessary for the different transmissions, K being the number of spreading sequences used previously before Q sequences from among K ($Q < K$) were made available.

32. (Previously presented)

A method according to

claim 31 which further includes;

calculating the cost functions $J^{(j, \Omega_k)}$ for any spreading sequence $c^{(j)}$ where j belongs to the set Ω_Q of the indices of the sequences made available,

calculating the cost functions $J^{(j, \Omega_k)}$ for any spreading sequence $c^{(k)}$ where k belongs to the set Ω_{K-Q} of the indices of the sequences still used,

as long as there exists one or more spreading sequences of index $j_o \in \Omega_Q$ and one or more spreading sequences of index $k_o \in \Omega_{K-Q}$ such that $J^{(j_o, \Omega_k)} < J^{(k_o, \Omega_k)}$ de-allocating the sequence $c^{(k_M)}$ defined by:

$$k_M = \arg \max_k [J^{(k, \Omega_k)}],$$

and allocating instead the sequence $c^{(k_M)}$ defined by:

$$k_m = \arg \max_k [J^{(k, \Omega_k)}].$$

33. (Previously presented) Assigning method according to Claim 31, which further includes;

calculating the cost functions $J^{(j, i_0)}$ for any spreading sequence $c^{(j)}$ where j belongs to the set Ω_Q of the indices of the sequences

made available,

calculating the cost functions $J^{(k,i_0)}$ for any spreading sequence $c^{(k)}$ where k belongs to the set Ω_{K-Q} of the indices of the sequences still used,

as long as there exists one or more spreading sequences of index $j_0 \in \Omega_Q$ and one or more spreading sequences of index $k_0 \in \Omega_{K-Q}$ such that $J^{(j_0,i_0)} < J^{(k_0,i_0)}$, de-allocating the sequence $c^{(k_M)}$ defined by:

$$k_M = \arg \max_k [J^{(k,i_0)}],$$

and allocating instead the sequence $c^{(k_m)}$ defined by:

$$k_m = \arg \min_k [J^{(k,i_0)}].$$

34. **(Currently Amended)** A transmitter for a Multi-Carrier Code Division Multiple Access transmission system, ~~of the type having means for multiplying a user data item by each of the elements of at least one spreading sequence and means for modulating on a sub-carrier each of the signals originating from the multiplication means, wherein the improvement comprises:~~

~~means for assigning to the user at least one spreading sequence, and~~

~~means for utilizing a minimization function to minimize the interference caused between the at least one sequence assigned to the user and a predetermined set of spreading sequences assigned by the transmitter~~ that assigns one or more spreading sequences among a family of spreading sequences to a user of a Multi-Carrier Code Division Multiple Access transmission network, each element of said sequence being, at the level of a transmitter of said network, multiplied by a data item to be transmitted and then transmitted on a corresponding sub-carrier, the transmitter comprising:

means for assigning, to said user, said one or more spreading sequences; and

means for minimizing a function representing the interference between said one or more sequences, on the one hand, and spreading sequences of a predetermined set, on the other hand, said predetermined set being included in said family of spreading sequences.